

# GEKKO®

State-of-the-art phased-array flaw detector with TFM



# SPECIFICATIONS

GENERAL		I/O	
L x W x H: 410mm x 284mm x 126mm	10.4" high contrast resistive screen Resolution 1024x768 px	1 IPEX connector for phased-array (can be upgraded to 2 with splitter)	4 LEMO 00 connectors for UT-TOFD (4PR)
Operating temperature range: from -10°C to 45°C   14°F to 113°F	Weight: 6kg (without battery) 0.480g /battery	3 encoder inputs	1 external trigger
Storage temperature range: -10°C to 60°C   14°F to 140°F with battery	Designed for IP66	3 USB 2.0	Remote control and data transfer through Ethernet
Operating time: 4h (hot swappable battery)	Shock resistance according to MIL-STD-810G	1 RJ 45 Ethernet connector	16 analog I/O

PHASED-ARRAY	
Maximum active aperture: 64 elements	Linear scanning, sectorial scanning, compound scanning, CIVA Laws
Total number of channels : 64	Focusing modes: true depth, sound path, projection
Linear, matrix, DLA and DMA probes	CIVA fueled phased-array calculator
Up to 6 probes   Up to 8 groups   Up to 2,048 delay-laws	On-board focal law calculation on plate, cylinder, T & Y, nozzle

REAL-TIME TFM	
Reconstruction channels: up to 64 elements	Max number of points of the TFM image: up to 1Mpi (post-processing)
Max refresh rate: up to 80fps	Sound paths: direct (L or S), indirect and converted modes
Real-time Adaptive TFM (ATFM) module	4 resolution levels
All calibration wizards (including TCG) available	A-Scan, B-Scan, C-Scan, D-Scan, Echodynamic, Top view, Side view, 3D view

PULSERS			
Phased array channels <sup>1</sup> :	Negative square pulse, width: 35ns to 1250ns	UT-TOFD channels <sup>2</sup> :	Negative square pulse, width: 30ns to 1250ns
	HT voltage: from 12V to 100V (with IV step)		HT voltage: from 12V to 200V (with IV step)
	Max. PRF: up to 20kHz		Max. PRF: up to 20kHz

RECEIVERS			
Phased array channels <sup>1</sup> :	Input impedance: 50 Ω	UT-TOFD channels <sup>2</sup> :	Input impedance: 50 Ω
	Frequency range: 0.4 to 20MHz		Frequency range: 0.6 to 25MHz
	Max. input signal: 1.2Vpp		Max. input signal: 1.4 Vpp
	Gain: up to 120dB (0.1dB step)		Gain: up to 120dB (0.1dB step)
	Cross-talk between two channels < 50 dB		

DIGITIZER	
Digitizing and real-time summation on 64 channels	16bits amplitude resolution
FIR filters	Max. sampling frequency: 100 MHz
Real-time averaging up to x32	Digitizing depth up to 16k samples
Rectified, RF, envelope	A-scan range or delay max 65k samples

ACQUISITION	
Hardware acquisition gates (true-depth or soundpath)	Max. data flow 150 MB/s on a 128Gb SSD (extensible up to 1 To)
A-Scan/Peak data recording	Data compression
FMC recording	Inspection data file size: SSD limitation
Acquisition trigger on time, event, encoder	Data frame loss indication

WIZARDS	
CAD overlay and 3D view	Scanner resolution calibration
Real-time phased array calculator	Amplitude calibration (TCG, ACG, DAC, DGS)
Base-time calibration for conventional UT & PA	Probe design   Weld geometry design
Wedge calibration (angle, height, velocity)	Amplitude balancing, dead element check
Specimen velocity calibration	Part geometry with parametric shapes: plate, cylinder, T & Y, nozzle

ANALYSIS	
Capture™ software with analysis and reporting tools – Free PC Viewer	Compatibility with CIVA analysis and Enlight™
A-Scan, B-Scan, C-Scan, D-Scan, Echodynamic, Top view, Side view, 3D view	Part & weld overlay: plate, cylinder, T or Y section, nozzle
Analysis gates	Digital gain, measurement indicators
TOFD Lateral wave linearization and removal	Customizable inspection report
Csv data export	Amplitude range: up to 800%

<sup>1</sup> Standard: EN ISO 18563-1 for phased array channels, / <sup>2</sup> Standard: EN ISO 12668-1 for conventional channels.

The information in this document is accurate as of its publication. Actual products may differ from those presented herein.



©2018 Eddyfi Technologies. M2M, Capture, Enlight, and their associated logos are trademarks or registered trademarks of Eddyfi Technologies in the United States and/or other countries. Eddyfi Technologies reserves the right to change product offerings and specifications without notice. 2018-05-28

www.m2m-ndt.com

contact-m2m@eddyfi.com

